

TABLE OF CONTENTS

	Page
ABSTRACT (THAI)	I
ABSTRACT (ENGLISH)	II
ACKNOWLEDGEMENTS.....	III
TABLE OF CONTENTS.....	IV
LIST OF TABLES	VIII
LIST OF FIGURES	IX
SYMBOLS AND ABBREVIATIONS	XIII
CHAPTER	
I INTRODUCTION.....	1
1.1 Background and Rationale.....	1
1.2 Research Objectives.....	1
1.3 Scope and Limitations.....	2
1.4 Research Methodology.....	3
1.4.1 Literature review	3
1.4.2 Samples preparation	3
1.4.3 Particle size analyses and classification	4
1.4.4 Microscopic examination	4
1.4.5 Mechanical properties testing	4
1.4.6 Hydraulic properties tests	5
1.4.8 Thesis writing.....	6
1.5 Thesis contents.....	6

TABLE OF CONTENTS (Continued)

	Page
II LITERATURE REVIEW.....	7
2.1 Introduction	7
2.2 Effect of mechanical in cement mixture of stone dust	7
2.2.1 Effect of particle size	9
2.2.2 Effect of particle shape.....	12
2.3 Application of stone dust mixture	12
2.4 Effect of mechanical and hydraulic properties on bentonite and aggregate mixtures.....	15
2.4.1 Compaction	14
2.4.2 Direct shear test.....	15
2.4.3 Consolidation test	17
2.4.4 Swelling test	18
2.5 Permeability properties of stone dust	19
2.6 Weight ratio of bentonite-stone dust mixture.....	20
III SAMPLE PREPARATION	21
3.1 Introduction	21
3.2 Rock Description	21
3.3 Sample preparation	21
IV MATERIAL CLASSIFICATION AND LABORATORY TESTING.....	25
4.1 Introduction	25
4.2 Grains size classification	25
4.2.1 Sieve analysis	25
4.2.2 Mixture procedure.....	29

TABLE OF CONTENTS (Continued)

	Page
4.3 Uniaxial compression tests.....	30
4.3.1 Test method.....	30
4.3.2 Uniaxial compression test results.....	32
V LABORATORY TESTING	41
5.1 Introduction	41
5.2 Compaction test	41
5.2.1 Test method.....	41
5.2.2 Test results	42
5.3 Direct Shear test	44
5.3.1 Test method.....	44
5.3.2 Test results	45
5.4 Consolidation test	48
5.4.1 Test method.....	48
5.4.2 Test results	49
5.5 Swelling test	50
5.5.1 Swelling tests under different bentonite weight ratios	50
5.5.2 Swelling test under different constant loads.....	52
5.6 Permeability test under falling head.....	54
5.6.1 Test method.....	54
5.6.3 Test results	56
VI DISCUSSIONS, CONCLUSIONS AND RECOMMENDATIONS	
FOR FUTURE STUDIES.....	60
7.1 Discussions	59
7.2 Conclusions.....	61

TABLE OF CONTENTS (Continued)

	Page
7.3 Recommendations for future studies.....	62
REFERENCE	63
APPENDIX A	72
BIOGRAPHY	78

LIST OF TABLES

Table	Page
3.1 Mineral compositions from XRD analysis.....	23
3.2 Particle shape classification of stone dust particles based on Powers (1982).....	25
4.1 Stone dust and clean sand classification based on USCS.....	27
4.2 Ranges of stone dust and clean sand sizes for stage I separation.....	28
4.3 Ranges of stone dust and clean sand sizes for stage II separation.....	29
4.4 Stone dust-cement mixtures specimens of stage I prepared for compression tests.....	32
4.5 Stone dust-cement mixtures specimens of stage II prepared for compression tests.	32
4.6 Uniaxial compressive strength test results of stage I	41
4.7 Uniaxial compressive strength test results of stage II.....	41
5.1 Compaction test results.....	45
5.2 Direct shear test results of fine-grained stone dust-bentonite mixtures results.....	48
5.3 Test results of permeability under falling head of each particle sizes.....	58

LIST OF FIGURES

Figure	Page
1.1 Research methodology.....	3
2.1 Variation of compressive strengths with gradual increase percentage of stone dust (Suman., 2018).....	9
2.2 Compressive strengths of cement cube concrete with percentage replacement of NS to SD (Rajput., 2018).....	9
2.3 Particle size distribution of Portland cement, fly ash and limestone stone dust (left) and compressive strength of the selected SCCs (right) presented by (Ghafoori et al., 2016).....	11
2.4 (a) Strength development and effect of (b) limestone content and (c) w/c ratio on 28-day cube strength of Portland cement and Portland limestone cement concretes (curing; 20°C water). (Dhir et al., 2007).....	11
2.5 SEM of dried samples at magnification factors of 75x; a) with sand 100%, b) with bentonite 5%, and c) with bentonite 50% (Proia et al., 2016).....	16
2.6 Illustration of particle shape parameters (Yanrong, 2013).....	17
2.7 Shear stress versus shear displacement response of different sands (Vangla and Latha, 2015).....	18
2.8 Three level grain matrix infill illustration (Horak et al., 2017).....	20
2.9 Microstructural examination of S-B and MD-B mixes Jain et al. (2022).....	21
3.1 Particle size distributions of stone dust.....	23
3.2 Examples of representative size and stone dust particles.....	24

LIST OF FIGURES (Continued)

Figure	Page
3.3 Estimation of roundness and sphericity of sedimentary particles (Powers,1982).....	24
4.1 Particle size distributions of stone dust and clean sand used in this study.....	27
4.2 Separations of particle size ranges for cement mixtures for stage I testing.....	28
4.3 Separations of particle size ranges for cement mixtures for stage II testing.....	29
4.4 Cement mixer to mix all components in mechanical properties test.....	30
4.5 Example image of cement cast (a) and cement mixture specimens (b).....	30
4.6 Laboratory arrangement for compression testing.....	31
4.7 Post-test specimens of stage I for uniaxial compressive strength.....	34
4.8 Post-test specimens of stage II for uniaxial compressive strength.....	35
4.9 Stress-strain curves of stage I for size ranges of 4.75-2.0, 2.0-0.85, 0.85-0.425, 0.425-0.25, 0.25-0.15, 0.15-0.075, 4.75-0.075 and clean sand (mm). as shown in (a) thought (h).....	36
4.10 Stress-strain curves of stage II for size ranges of 4.75-0.25, 4.75-0.15, 0.25-0.15, 0.15-0.075, and clean sand (mm). as shown in (a) thought (e).....	37
4.11 Compressive strengths of stone dust mixed with cement of stage I (a), and stage II (b).....	38
4.12 Elastic modulus of stone dust mixed with cement of stage I (a), and stage II (b).....	39

LIST OF FIGURES (Continued)

Figure	Page
4.13 Elastic modulus of stone dust mixed with cement of stage I (a), and stage II (b).....	40
5.1 Fine-grained stone dust mixed with bentonite prepared in plastic tray.....	42
5.2 Compaction mold based on ASTM D1557-12 (2021) standard method.....	43
5.3 Maximum dry density as a function of water content for various stone dust bentonite mixing ratios.....	44
5.4 Maximum unit weight as a function of fine-grained stone dust-bentonite weight ratio comparing before and after compaction.....	44
5.5 Optimum water content as a function of fine-grained stone dust- bentonite weight ratio.....	45
5.6 Direct shear device of fined-aggregates stone dust-mixed bentonite testing using by direct shear machine.....	46
5.7 Shear stress as a function of shear displacement of fine-grained stone dust- bentonite mixtures.....	47
5.8 Shear strengths as a function normal stress.....	47
5.9 The cohesions and friction angles of specimens mixtures for the first separator (set I).....	48
5.10 Consolidation testing of fined-aggregates stone dust-mixed bentonite testing using by Soil test pro machine.....	49
5.11 Void ratio as a function of effective stress of fine-grained stone dust-bentonite mixtures.....	50
5.12 Swelling test setup in compaction mold.....	52
5.13 Swelling ratio as a function of time.....	52

LIST OF FIGURES (Continued)

Figure	Page
5.14 Swelling ratios of fined grained stone dust-bentonite mixtures as a function of time under loads of 2 kg (a), 4 kg (b) and 6 kg (c).....	54
5.15 Swelling ratios of fined grained stone dust-bentonite mixtures as a function of static load.....	55
5.15 Swelling ratios of fined grained stone dust-bentonite mixtures as a function of static load.....	55
5.16 Permeability test apparatus of stone dust under falling head.....	56
5.17 Average coefficient of permeability of each sieve mesh no.....	59

SYMBOLS AND ABBREVIATIONS

σ_c	=	Uniaxial compressive strength
E	=	Young's modulus
ν	=	Poisson's ratio
SD	=	Stone dust
C	=	Cement
B	=	Bentonite
ρ_{dry}	=	Maximum dry unit weight
ϕ	=	Angle of friction
σ_n	=	Normal stress
ϵ	=	Strain
XRD	=	X-ray diffraction
c	=	Cohesion
k	=	hydraulic conductivity
a_m	=	Internal cross-sectional area of standpipe
L	=	Length of soil sample
A	=	Sample area
t	=	Total time of discharge
h_1	=	Initial water level
h_2	=	Final water level
k_t	=	Coefficient of permeability for a test temperature of water at $T^\circ C$
η_t	=	Viscosities at the temperature $T^\circ C$ of the test
η_{20}	=	Viscosities at the temperature $20^\circ C$ of the test
h	=	Difference in head on manometers