LIST OF TABLES

Table		Page
2.1	Summarization techniques for accessing erosion process	9
3.1	Mineral compositions of samples before testing	
4.1	Roundness classifications	
4.2	Sphericity classifications	44
5.1	Mean roundness, sphericity, and average sizes with standard deviation for PWSS, PPCS and PPSS specimens under dry and wet tests	51
5.2	Mineral compositions in terms of weight percent (W_i) for retained fragments before testing and after 80 test cycles	55
5.3	Mineral compositions in terms of volumatic percent (V_i) for retained fragments before testing and after 80 test cycles	56
5.4	Mineral compositions in terms of weight percent (V_i) for passing material after test cycle 40 and 80	59
5.5	Densities for PWSS, PPCS and PPSS specimens before testing and after test cycle 20, 40, 60, and 80	60
6.1	Normalized fragment sizes for PWSS, PPCS and PPSS specimens before testing and after test cycle 20, 40, 60, and 80	63
6.2	Calculated porosities (n_c) and porosities (n) for PWSS, PPCS and PPSS specimens before testing and after testing through 80 cycles. The n_c	
	is measured with an interval of 20 test cycles	66
6.3	Test cycle (N) required to obtain 100% passing materials	71

LIST OF TABLES (continued)

Table	e	Page
7.1	Parameters of testing drum	75
7.2	Prediction of accumulated energy (E) and test cycle (N) required to	
	obtain 100% passing materials with 2 mm or less	76
7.3	Constant parameters using in equation (7.10) through (7.12)	78