

TABLE OF CONTENTS

	Page
ACKNOWLEDGMENTS	v
TABLE OF CONTENTS	vi
LIST OF TABLES	x
LIST OF FIGURES	ix
CHAPTER	
I. INTRODUCTION	ix
1.1 Background and problem.....	1
1.2 Research objectives.....	1
1.3 Goals.....	2
1.4 Scope and limitations	3
1.4.1. Limitations of the study.....	3
1.5 Research benefits.....	4
II. LITERATURE REVIEW	6
2.1 Introduction.....	6
2.2 Transportation damage.....	6
2.3 Impact damage.....	7
2.4 Impact damage to fresh produce	7
2.4.1. Package cushioning.....	8
2.5 Finite element method.....	9

TABLE OF CONTENTS(Continued)

	Page
2.5.1. Differential equation	10
2.6 FEM for solid mechanics problems.....	10
2.6.1. Surface traction.....	11
2.6.2. Three-dimensional isoperimetric elements.	14
2.7 Mesh generation.....	14
2.8 Failure theories of material.....	15
2.8.1. Brittle fracture	16
2.8.2. Ductile fracture	16
2.8.3. Triaxial stress	17
2.8.4. Von-Mises yield criteria.	19
III. METHODOLOGY	21
3.1 Material	21
3.1.1. NRL Foam.....	21
3.1.2. Cushioning materials and testing	23
3.1.3. Testing Method.....	23
3.1.4. Mechanical Characterization of Guava.....	27
3.1.5. Characterization of Mechanical Properties.....	27
3.1.6. Poisson's ratio.....	30
3.2 Computer-aided design	34
3.3 Finite element analysis	34
3.3.1. Model Analysis.....	34

TABLE OF CONTENTS(Continued)

	Page
3.3.2. Preprocess.....	35
3.4 Validation.....	45
3.4.1. Boundary Conditions Setting for Validation	47
IV. RESULTS AND DISCUSSION.....	51
4.1 Introduction.....	51
4.2 Parameter variation and result.....	51
4.3 Effect of size and number on cushion performance.....	55
4.4 Density Reduction Effects on Impact Protection.....	63
V. CONCLUSIONS.....	73
5.1 Conclusion.....	73
5.2 Suggestions.....	75
REFERENCES.....	77
BIOGRAPHY.....	79

LIST OF TABLES

Table	Page
3.1. Formulation of the natural rubber latex (NRL) compounds for the synthesis of reinforcing NRL foam (NRLF).....	21
3.2 Compressive stress at 50% Strain of foam samples	26
3.3 Mechanical properties of foam samples and guava	33
3.4 Direction of setting standard earth gravity	40
3.5 Material parameters	40
3.6 Mesh method and element size	42
3.7 Mesh convergence	45
3.8 Material properties for the drop test simulation analysis	48
3.9 Comparison of experimental and simulated bruise areas	49
4.1 Relationship between number of filaments, density, and weight	72

LIST OF FIGURES

Figure	Page
2.1 The process of computer aid designs and numerical techniques	9
2.2 Workflow of pre-processing FEM simulation.....	9
2.3 Triaxial Stress State (James Gere, 2008.).....	11
2.4 The traction vector (T), (stress vector at the point) on the surface surrounding the point with normal vector $\mathbf{n}$ is defined as.....	12
2.5 Rigid body equilibrium 3D.....	13
2.6 Finite element mesh of quadrilaterals of a curved domain.	15
2.7 Mesh generation	15
2.8 Stress-strain curves of brittle material, ductile material-compression test.....	16
2.9 Diagram failure theories of material	17
2.10 Triaxial stress state mechanics of materials (James Gere, 2008).....	17
2.11 failure envelope as per maximum shear stress theory	19
2.12 Comparison of the yield locus for the plane stress of von Mises yield criterion and Tresca yield criterion.	20
3.1 Flowchart of processing step NRL foam	22
3.2 Sample cube specimen of 50 mm X 50 mm X 25 mm used in the study.....	24
3.3 Universal testing machine (INSTRON/5565, Norwood, MA, USA).	25
3.4 Stress-strain curve of the EPE and NRLF foam obtained using a compression test.	25
3.5 Sample cube specimen of 50 mm X 50 mm X 25 mm follower ASTM D3574 test C under compression testing.	26
3.6 Stress-strain curve of the EPE foam obtained using a compression test.....	26

LIST OF FIGURES(Continued)

Figure	Page
3.7 (a) Guava fruit (<i>Psidium guajava</i> L.) cv. Glom Sali (b) Sample cube specimen of guava (<i>Psidium guajava</i> L.) using in the present study sample size 20 mm x 20 mm.	28
3.8 Stress-strain curve of the Guava (<i>Psidium guajava</i> L.) obtained using a compression test.	30
3.9 The Poisson's ratio of a material.....	30
3.10 A cube made of an isotropic linearly elastic material is stretched along	31
3.11 Schematic explanation of the two-dimensional poisson effect	31
3.12 Sample cube specimen of guava (<i>Psidium guajava</i> L.) using in the present study sample size 20 mm x 20 mm.	32
3.13 Determine of NRLF negative Poisson's ratio using UTM.	32
3.14 Force displacement curve of Guava fruit (<i>Psidium guajava</i> L.) Glom Sali	33
3.15 Flow chart of CAD/CAE design analysis (Chang. 2013).....	34
3.16 Guava with commercial expanded polyethylene foam net CAD Modeling NRLF net foam cushion.....	35
3.17 CAD cushion foam net 20 mesh filament number on NRLF 3.5 mm	36
3.18 CAD model guava with expanded polyethylene cushion foam net	36
3.19 Simplifications of simulation model.....	37
3.20 3D model of commercial cushion foam net	38
3.21 CAD 3D model filament dimension 3.5 mm (number a:25, b: 20, and c: 15 filament).....	38
3.22 FEM model for simulating with the impact plane drop test.....	39
3.23 FEM model boundary conditions drop high setting	40

LIST OF FIGURES(Continued)

Figure	Page
3.24 Finite element model (a) reverse-engineered guava cushion foam net model, outer mesh structure, (b) inner mesh structure)	41
3.25 Show cross section in meshing setup of EPE cushion net foam 3.5X25 mm and guava mesh size 3.00mm	42
3.26 Effect of mesh size, Nodes, and elements on CAD model of NRLF cushion net foam 3.5 mm 25x25.....	43
3.27 Mesh sensitivity analysis	44
3.28 The experimental fruit bruise damage.....	47
3.29 Validation model using FEM Drop test simulation setup.....	48
4.1 Stress [MPa] in the gravity direction for the drop height 200 mm model (a) guava unpacking (b) guava with EPE commercial cushion	53
4.2 Maximum von-miss equivalent stress of guava and time at 0.016 s. drop height of 200 mm.	54
4.3 Maximum (von-miss) drop test of guava bear fruit compared to EPE commercial cushion foam net.	54
4.4 Stress in the gravity direction for the drop height model (a) NRLF 2.5x15, (b) NRLF 2.5x20 and (c) NRLF 2.5x25 from a cross-section view.....	56
4.5 Stress distribution plots in guava sample (max von-mises stress, [MPa]) of NRLF foam net diameter filament size 2.5 mm.	57
4.6 Stress [MPa] in the gravity direction for the drop height model (a) NRLF 3.5x15, (b) NRLF 3.5x20 and (c) NRLF 3.5x15 from a cross-section view show at time 0.0012 s.....	58
4.7 Stress distribution plots in guava sample (max von-mises stress, [MPa]) of NRLF foam net diameter filament size 3.5 mm.	59

LIST OF FIGURES(Continued)

Figure	Page
4.8 Stress [MPa] in the gravity direction for the drop height model (a) NRLF 4.5x15, (b) NRLF 4.5x20 and (c) NRLF 4.5x15 from a cross-section view show at time 0.0012 s.....	60
4.9 Stress distribution plots in guava sample (max von-mises stress, [MPa]) of NRLF foam net diameter filament size 4.5 mm.	61
4.10 Maximum (von-miss) drop test of Guava NRLF packaging.....	61
4.11 Maximum equivalent stress drop test 200 mm was observed at 0.013 s after impact and NRLF filament number 25....	62
Figure 4.12 Maximum equivalent stress drop test 200 mm was observed at 0.013 s after impact of bear fruit and EPE...	63
4.13 Stress [MPa] in the gravity direction for the drop height 100 mm filaments number 25 and the density (kg/m^3) (a) 420, and (b) 397 from a cross-section view.	65
4.14 Stress [MPa] in the gravity direction for the drop height 100 mm filaments number 25 and the density (kg/m^3) (a) 420, (b) 397, and (c) 345 from a cross-section view.....	66
4.15 Plot Maximum stress (MPa) Time (s) plot for the model of filaments number 25 of and the density (kg/m^3) 420, 397, and 345.....	66
4.16 Stress in the gravity direction for the drop height 100 mm filaments number 20 and the density (kg/m^3) (a) 420, and (b) 397 from a cross-section view.	67
4.17 Stress in the gravity direction for the drop height 100 mm filaments number 20 and the density (kg/m^3) (a) 420, (b) 397, and (c) 345 from a cross-section view (Continued).	68
4.18 d) Maximum stress (MPa) Time (s) plot for the model of filaments number 20 of and the density (kg/m^3) 420, 397, and 345.....	68

LIST OF FIGURES(Continued)

Figure	Page
4.19 Stress [MPa] in the gravity direction for the drop height 100 mm filaments number 15 and the density (kg/m^3) a) 420, and b) 397 from a cross-section view	69
4.20 Stress [MPa] in the gravity direction for the drop height 100 mm filaments number 15 and the density (kg/m^3) c) 345 from a cross-section view (Continued).	70
4.20 Stress [MPa] in the gravity direction for the drop height 100 mm filaments number 15 and the density (kg/m^3) c) 345 from a cross-section view (Continued).	70
4.21 Maximum stress (MPa) Time (s) plot for the model of filaments number 15 of and the density (kg/m^3) 420, 397, and 345.	71
4.22 Maximum stress values for samples with filament numbers 15, 20, and 25, and densities of 420, 397, and 345 kg/m^3 drop test 100 mm was observed at 0.013 s after impact.	77