

REFERENCES

- G. Halmetschlager-Funek, M. Suchi, M. Kampel, and M. Vincze, "An empirical evaluation of ten depth cameras: Bias, precision, lateral noise, different lighting conditions and materials, and multiple sensor setups in indoor environments," *IEEE Robotics & Automation Magazine*, vol. 25, no. 3, pp. 1–1, Aug. 2018, doi: 10.1109/MRA.2018.2852795.
- P. Chen, X. Zhao, L. Zeng, L. Liu, and S. Liu, "A review of research on SLAM technology based on the fusion of LiDAR and vision," *Sensors*, vol. 25, no. 5, p. 1447, 2025, doi: 10.3390/s25051447.
- J. Gené-Mola, J. Llorens, J. R. Rosell-Polo, and E. Gregorio, "Assessing the performance of RGB-D sensors for 3D fruit crop canopy characterization under different operating and lighting conditions," *Sensors*, vol. 20, no. 24, p. 7072, 2020, doi: 10.3390/s20247072.
- Drone For Inspecting Inside Building With Object Avoidance And Mapping System (Pawarut Karaked, 2023)
- T. Shan and B. Englot, "LIO-SAM: Tightly-Coupled Lidar Inertial Odometry via Smoothing and Mapping," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2020, pp. 5135–5142.
- Kirchner, N., & Furukawa, T. (2005). Infrared localization for indoor uavs. Paper presented at the Proc. Of the 1st Int. Conf. on Sensing Technology
- Y. Lu, J. Xue, G. Xia, and L. Zhang, "A survey on vision-based UAV navigation," *Journal of Field Robotics*, 21(1), 21-32
- Mourikis, A. I., & Roumeliotis, S. I. (2007). A multi-state constraint Kalman filter for vision-aided inertial navigation. In *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)* (pp. 3565–3572).

Development of Autonomous Electric Golf Cart System for Passenger Transportation Between Building (Wongsathon Angkhem, 2023)

Zunaidi, I., Kato, N., Nomura, Y., & Matsui, H. (2006). Positioning system for 4-wheel mobile robot: Encoder, gyro and accelerometer data fusion with error model method. *CMU Journal*, 5(1), 1–14.

M. Quigley, B. Gerkey, K. Conley, J. Faust, T. Foote, J. Leibs, E. Berger, R. Wheeler, and A. Y. Ng, “ROS: An open-source Robot Operating System,” in *Proc. IEEE Int. Conf. on Robotics and Automation (ICRA) Workshop on Open Source Software*, Kobe, Japan, 2009.

ROS.(2024). REF-0105: Standard Unit of Measure and Coordinate Conventions

REP 103, Standard Unit of Measure and Coordinate Conventions

Foote, T. (2013). tf: The transform library. Paper presented at the 2013 IEEE Conference on Technologies for Practical Robot Applications (TePRA)

Thrun, S. (2007). Simultaneous localization and mapping. In *Robotics and cognitive approaches to spatial mapping* (pp. 13-41): Springer.

Thrun, S., Fox, D., Burgard, W., & Dellaert, F. (2001). Robust Monte Carlo localization for mobile robots. *Artificial intelligence*, 128 (1-2), 99-141.

Grisetti, G., Kummerle, R., Stachniss, c., & Burgard, W. (2010). A tutorial on graph-based SLAM. *IEEE Intelligent Transportation Systems Magazine*, 2(4), 31-43

Davison. (2003, October). Real-time simultaneous localization and mapping with single camera. In *proceedings Ninth IEEE International Conference on Computer Vision* (pp. 1403-1410). IEEE.

Berka, Z. (2020). *Mapping road makings and localization of F110 autonomous car using camera*. Retrieved from https://people.ciirc.cvut.cz/~klapajar/studenti/F3-DP-2020-Berka-Zdenek-Mapping_road_makings_and_localization_of_f110_autonomous_car_using_camera.pdf

- Saeefi. S., Liu, L., & Lee, S. (2020). *A review of SLAM algorithms and their applications*.Journal of Open Source Software, 5(52), 2783.
<https://doi.org/10.21105/joss.02783>
- [22] A. Zaarane, I. Slimani, W. Al Okaishi, I. Atouf, and A. Hamdoun, “Distance measurement system for autonomous vehicles using stereo camera,” *Array*, vol. 5, p. 100016, 2020, doi: 10.1016/j.array.2020.100016.