

ABSTRACT

The Navier-Stokes equations in the Oberbeck-Boussinesq approach are used for description convective flows of viscous incompressible fluids in a two-layer systems. A finite-difference method is utilized to developed the numerical algorithm for modeling buoyancy driven flow in cavity vertical or horizontal sides which are differentially heated. The algorithm is based on the method of splitting (O.M. Belotserkovskii, V.A.Gushin, V.V. Shennikov [1]). The approximation is carried out on a staggered grid. Critical comparison with benchmark solution [2] confirms the accuracy of method, and results for the buoyancy-driven flow in square cavity with vertical sides, which are differently heated, are presented for Rayleigh numbers of 10^6 . The results of two-dimensional (2-D) numerical simulations of thermal convection in two-layer system are compared with the experimental data of N.L. Dobretsov and A.G. Kirdyashkin [3]. The dependence of two-layer convection for wide range of relation of the viscosity, the thermal diffusivity and layer thickness was made.

บทคัดย่อ

แนวคิดของโอเบอร์เบค-บูลสึเนสก ได้ใช้สมการนาเวียร์ - สโตกส์ ศึกษาการไหลแบบพาของของไหลที่มีความหนืดและอัดตัวไม่ได้ในระบบการไหล 2 ชั้น ระเบียบวิธีการผลต่างสี่เหลี่ยมเป็นวิธีการหนึ่งที่ถูกนำมาพัฒนาตามขั้นตอนวิธีการเชิงตัวเลข สำหรับการไหลจำลองของแรงลอยตัวภายในอาณาบริเวณตามแนวตั้งและแนวนอน ด้วยความร้อนที่แตกต่างกัน วิธีการผลต่างสี่เหลี่ยมที่ใช้คือวิธีสปริทิง [O.M. Belotserkovskii, V.A. Gushin และ V.V. Shennikov [1]] การประมาณค่าพิจารณาตรงจุดที่เหลื่อมกัน แสดงการเปรียบเทียบความแม่นยำของผลเฉลยกับผลเฉลยที่ได้มีผู้วิจัยอื่นๆทำมาแล้ว ได้ผลลัพธ์ที่มีความถูกต้องตรงกัน ในกรณีของการไหลของแรงลอยตัวภายในช่องสี่เหลี่ยมจัตุรัสที่ตั้งตรงกับขนาดการไหลหมุนวน ซึ่งอยู่ในความร้อนที่แตกต่างกัน เมื่อกำหนดจำนวนเรเลย์ด์ (Rayleigh Numbers) เท่ากับ 10^6 งานวิจัยนี้แสดงผลการเปรียบเทียบวิธีการจำลองเชิงตัวเลขของการพาความร้อนในสองมิติในระบบการไหล 2 ชั้น กับผลที่ได้จากการทดลองของ N.L. Dobretsov และ A.G. Kirdyashkin [3] นอกจากนี้การศึกษากาความร้อนของของไหลในชั้นของของไหล 2 ชั้น ยังได้พิจารณาถึงตัวแปรต่างๆเช่น ความหนืด การกระจายความร้อนและความหนาของชั้นด้วย