

## REFERENCES

## REFERENCES

- Abdul Salim, Z. A. S., Hassan, A., & Ismail, H. (2018). A review on hybrid fillers in rubber composites. *Polymer-Plastics Technology and Engineering*, 57(6), 523-539.
- Aggarwal, P., Singh, R. P., & Aggarwal, Y. (2015). Use of nano-silica in cement based materials—A review. *Cogent Engineering*, 2(1), 1078018.
- Akbay, İ. K., Güngör, A., & Özdemir, T. (2018). Using fish scales (*Sardina pilchardus*) within ethylene - propylene - diene ter monomer rubber as bio - based filler. *Journal of Applied Polymer Science*, 135(39), 46698.
- Assaad, J. J. (2018). Development and use of polymer-modified cement for adhesive and repair applications. *Construction and Building Materials*, 163, 139-148.
- Azat, S., Korobeinyk, A., Moustakas, K., & Inglezakis, V. (2019). Sustainable production of pure silica from rice husk waste in Kazakhstan. *Journal of cleaner production*, 217, 352-359.
- Baghini, M. S., Ismail, A., Naseralavi, S. S., & Firoozi, A. A. (2016). Performance evaluation of road base stabilized with styrene-butadiene copolymer latex and Portland cement. *International Journal of Pavement Research and Technology*, 9(4), 321-336.
- Balan, A. K., Mottakkunnu Parambil, S., Vakyath, S., Thulisery Velayudhan, J., Naduparambath, S., & Etathil, P. (2017). Coconut shell powder reinforced thermoplastic polyurethane/natural rubber blend-composites: effect of silane coupling agents on the mechanical and thermal properties of the composites. *Journal of materials science*, 52, 6712-6725.
- Boonmahitthisud, A., & Chuayjuljit, S. (2012). NR/XSBR nanocomposites with carbon black and carbon nanotube prepared by latex compounding. *Journal of Metals, Materials and Minerals*, 22(1).

- Boonmahitthisud, A., Pokphat, P., Chaiwutthinan, P., & Chuayjuljit, S. (2017). Nanocomposites of NR/SBR blend prepared by latex casting method: effects of nano-TiO<sub>2</sub> and polystyrene-encapsulated nano-TiO<sub>2</sub> on the cure characteristics, physical properties, and morphology. *Journal of Nanomaterials*, 2017.
- Boonmee, A., & Jarukumjorn, K. (2020). Preparation and characterization of silica nanoparticles from sugarcane bagasse ash for using as a filler in natural rubber composites. *Polymer Bulletin*, 77(7), 3457-3472.
- Bureewong, N., Injorhor, P., Krasaekun, S., Munchan, P., Waengdongbang, O., Wittayakun, J., . . . Ruksakulpiwat, Y. (2023). Preparation and Characterization of Acrylonitrile Butadiene Rubber Reinforced with Bio-Hydroxyapatite from Fish Scale. *Polymers*, 15(3), 729.
- Bureewong, N., Ruksakulpiwat, Y., & Ruksakulpiwat, C. (2022a). IN SITU SILICA REINFORCED RUBBER LATEX COMPOSITE: EFFECTS OF BLEND RATIO AND SILICA CONTENT. *Suranaree Journal of Science & Technology*, 29(2).
- Bureewong, N., Ruksakulpiwat, Y., & Ruksakulpiwat, C. (2022b). *Mechanical and thermal properties of NR/XSBR composite reinforced with rice husk silica*. Paper presented at the Journal of Physics: Conference Series.
- Chuayjuljit, S., Nutchapong, T., Saravari, O., & Boonmahitthisud, A. (2015). Preparation and characterization of epoxidized natural rubber and epoxidized natural rubber/carboxylated styrene butadiene rubber blends. *Journal of Metals, Materials and Minerals*, 25(1).
- de Paiva, F. F. G., de Maria, V. P. K., Torres, G. B., Dognani, G., dos Santos, R. J., Cabrera, F. C., & Job, A. E. (2019). Sugarcane bagasse fiber as semi-reinforcement filler in natural rubber composite sandals. *Journal of Material Cycles and Waste Management*, 21, 326-335.
- Dhaneswara, D., Fatriansyah, J. F., Situmorang, F. W., & Haqoh, A. N. (2020). Synthesis of amorphous silica from rice husk ash: comparing HCl and CH<sub>3</sub>COOH acidification methods and various alkaline concentrations. *Synthesis*, 11(1), 200-208.

- Dung, L. T. K., Hien, N. Q., Van Phu, D., & Du, B. D. (2017). Preparation and characterization of nanosilica from rice husk ash by chemical treatment combined with calcination. *Vietnam Journal of Chemistry*, *55*(4), 455-455.
- Guo, W., Li, G., Zheng, Y., & Li, K. (2021). Nano-silica extracted from rice husk and its application in acetic acid steam reforming. *RSC advances*, *11*(55), 34915-34922.
- Inphonlek, S., Bureewong, N., Jarukumjorn, K., Chumsamrong, P., Ruksakulpiwat, C., & Ruksakulpiwat, Y. (2022). Preparation of Poly (acrylic acid-co-acrylamide)-Grafted Deproteinized Natural Rubber and Its Effect on the Properties of Natural Rubber/Silica Composites. *Polymers*, *14*(21), 4602.
- Ismail, M., Muhammad, B., & Mohamad, N. A. (2009). Durability performance of natural rubber latex modified concrete. *Malaysian Journal of Civil Engineering*, *21*(2).
- Jembere, A. L., & Fanta, S. W. (2017). Studies on the synthesis of silica powder from rice husk ash as reinforcement filler in rubber tire tread part: Replacement of commercial precipitated silica. *SMR*, *20*(70), 70.
- Jo, B.-W., Kim, C.-H., Tae, G.-h., & Park, J.-B. (2007). Characteristics of cement mortar with nano-SiO<sub>2</sub> particles. *Construction and Building Materials*, *21*(6), 1351-1355.
- Kato, H., Nakamura, A., & Noda, N. (2014). Determination of size distribution of silica nanoparticles: A comparison of scanning electron microscopy, dynamic light scattering, and flow field-flow fractionation with multiangle light scattering methods. *Materials Express*, *4*(2), 144-152.
- Keawkumay, C., Jarukumjorn, K., Wittayakun, J., & Suppakarn, N. (2012). Influences of surfactant content and type on physical properties of natural rubber/organoclay nanocomposites. *Journal of Polymer Research*, *19*, 1-9.
- Khan, K., Ullah, M. F., Shahzada, K., Amin, M. N., Bibi, T., Wahab, N., & Aljaafari, A. (2020). Effective use of micro-silica extracted from rice husk ash for the production of high-performance and sustainable cement mortar. *Construction and Building Materials*, *258*, 119589.
- Knapen, E., & Van Gemert, D. (2015). Polymer film formation in cement mortars modified with water-soluble polymers. *Cement and Concrete Composites*, *58*, 23-28.

- Kobler, J., Möller, K., & Bein, T. (2008). Colloidal suspensions of functionalized mesoporous silica nanoparticles. *Acs Nano*, 2(4), 791-799.
- Loykaew, A., & Utara, S. (2020). Effect of acidic and sulfated environments on phase transformation, compressive strength and microstructure of natural rubber latex-modified cement pastes. *Journal of Materials Research and Technology*, 9(6), 15496-15512.
- Majumder, C., Sharma, M., & Soni, G. (2014). A simple non-conventional method to extract amorphous silica from rice husk. *Bioresource Technology*, *accepted*, 28.
- Muhammad, B., Ismail, M., Haron, Z., & Ali Yussuf, A. (2011). Elastomeric effect of natural rubber latex on compressive strength of concrete at high temperatures. *Journal of materials in civil engineering*, 23(12), 1697-1702.
- Nawamawat, K., Sakdapipanich, J. T., Ho, C. C., Ma, Y., Song, J., & Vancso, J. G. (2011). Surface nanostructure of Hevea brasiliensis natural rubber latex particles. *Colloids and Surfaces A: Physicochemical and Engineering Aspects*, 390(1-3), 157-166.
- Nihmath, A., & Ramesan, M. (2017). Fabrication, characterization and dielectric studies of NBR/hydroxyapatite nanocomposites. *Journal of Inorganic and Organometallic Polymers and Materials*, 27, 481-489.
- Nihmath, A., & Ramesan, M. (2018). Preparation, characterization, thermal, and electrical properties of chlorinated ethylene propylene diene monomer/hydroxyapatite nanocomposites. *Polymer Composites*, 39(6), 2093-2100.
- Nihmath, A., & Ramesan, M. (2020). Hydroxyapatite as a potential nanofiller in technologically useful chlorinated acrylonitrile butadiene rubber. *Polymer Testing*, 91, 106837.
- Nihmath, A., & Ramesan, M. T. (2021). Development of hydroxyapatite nanoparticles reinforced chlorinated acrylonitrile butadiene rubber/chlorinated ethylene propylene diene monomer rubber blends. *Journal of Applied Polymer Science*, 138(15), 50189.
- Ohama, Y., & Ramachandran, V. (1996). Polymer-modified mortars and concretes. In *Concrete admixtures handbook* (pp. 558-656): Elsevier.

- Phumnok, E., Khongprom, P., & Ratanawilai, S. (2022). Preparation of natural rubber composites with high silica contents using a wet mixing process. *ACS omega*, 7(10), 8364-8376.
- Pode, R. (2016). Potential applications of rice husk ash waste from rice husk biomass power plant. *Renewable and Sustainable Energy Reviews*, 53, 1468-1485.
- Rabiei, S., & Shojaei, A. (2016). Vulcanization kinetics and reversion behavior of natural rubber/styrene-butadiene rubber blend filled with nanodiamond–The role of sulfur curing system. *European Polymer Journal*, 81, 98-113.
- Rajan, V., Dierkes, W. K., Joseph, R., & Noordermeer, J. W. (2006). Science and technology of rubber reclamation with special attention to NR-based waste latex products. *Progress in Polymer Science*, 31(9), 811-834.
- Rupasinghe, M., San Nicolas, R., Mendis, P., Sofi, M., & Ngo, T. (2017). Investigation of strength and hydration characteristics in nano-silica incorporated cement paste. *Cement and Concrete Composites*, 80, 17-30.
- Shen, Y. (2017). Rice husk silica derived nanomaterials for sustainable applications. *Renewable and Sustainable Energy Reviews*, 80, 453-466.
- Shen, Y., Zhao, P., & Shao, Q. (2014). Porous silica and carbon derived materials from rice husk pyrolysis char. *Microporous and Mesoporous Materials*, 188, 46-76.
- Srisuwan, L., Jarukumjorn, K., & Suppakarn, N. (2018). Effect of silane treatment methods on physical properties of rice husk flour/natural rubber composites. *Advances in Materials Science and Engineering*, 2018.
- Staudt, Y., Odenbreit, C., & Schneider, J. (2018). Failure behaviour of silicone adhesive in bonded connections with simple geometry. *International Journal of Adhesion and Adhesives*, 82, 126-138.
- Stephen, R., Raju, K., Nair, S. V., Varghese, S., Oommen, Z., & Thomas, S. (2003). Mechanical and viscoelastic behavior of natural rubber and carboxylated styrene - butadiene rubber latex blends. *Journal of Applied Polymer Science*, 88(11), 2639-2648.

- Sukmak, G., Sukmak, P., Horpibulsuk, S., Yaowarat, T., Kunchariyakun, K., Patarapaiboolchai, O., & Arulrajah, A. (2020). Physical and mechanical properties of natural rubber modified cement paste. *Construction and Building Materials*, *244*, 118319.
- Tangudom, P., Thongsang, S., & Sombatsompop, N. (2014). Cure and mechanical properties and abrasive wear behavior of natural rubber, styrene-butadiene rubber and their blends reinforced with silica hybrid fillers. *Materials & Design*, *53*, 856-864.
- Thiele, G., Poston, M., & Brown, R. (2010). A case study in sizing nanoparticles. *Micromeritics Instrument Corporation*. Available online: <http://www.particletesting.com/library> (accessed on 1 January 2019).
- Thommes, M., Kaneko, K., Neimark, A. V., Olivier, J. P., Rodriguez-Reinoso, F., Rouquerol, J., & Sing, K. S. (2015). Physisorption of gases, with special reference to the evaluation of surface area and pore size distribution (IUPAC Technical Report). *Pure and applied chemistry*, *87*(9-10), 1051-1069.
- Thuadajj, N., & Nuntiya, A. (2008). Synthesis and characterization of nanosilica from rice husk ash prepared by precipitation method. *J. Nat. Sci. Special Issue on Nanotechnology*, *7*(1), 59-65.
- Vo, M. L., & Plank, J. (2018). Evaluation of natural rubber latex as film forming additive in cementitious mortar. *Construction and Building Materials*, *169*, 93-99.
- Vu, C. M., Vu, H. T., & Choi, H. J. (2015). Fabrication of natural rubber/epoxidized natural rubber/nanosilica nanocomposites and their physical characteristics. *Macromolecular Research*, *23*, 284-290.
- Wang, M., Wang, R., Yao, H., Farhan, S., Zheng, S., Wang, Z., . . . Jiang, H. (2016). Research on the mechanism of polymer latex modified cement. *Construction and Building Materials*, *111*, 710-718.
- Wang, R., Ma, D., Wang, P., & Wang, G. (2015). Study on waterproof mechanism of polymer-modified cement mortar. *Magazine of Concrete Research*, *67*(18), 972-979.
- Wei, Y., Zhang, H., Wu, L., Jin, L., & Liao, S. Q. (2017). *A review on characterization of molecular structure of natural rubber*.

- Wongsorat, W., Suppakarn, N., & Jarukumjorn, K. (2014). Effects of compatibilizer type and fiber loading on mechanical properties and cure characteristics of sisal fiber/natural rubber composites. *Journal of Composite Materials*, 48(19), 2401-2411.
- Yaowarat, T., Suddeepong, A., Hoy, M., Horpibulsuk, S., Takaikaew, T., Vichitcholchai, N., . . . Chinkulkijniwat, A. (2021). Improvement of flexural strength of concrete pavements using natural rubber latex. *Construction and Building Materials*, 282, 122704.
- Yin, C., Zhang, Q., Liu, J., Gao, Y., Sun, Y., & Zhang, Q. (2019). Preparation and characterization of grafted natural rubber/graphene oxide nanocomposites. *Journal of Macromolecular Science, Part B*, 58(7), 645-658.
- Yuvakkumar, R., Elango, V., Rajendran, V., & Kannan, N. (2014). High-purity nano silica powder from rice husk using a simple chemical method. *Journal of experimental nanoscience*, 9(3), 272-281.
- Zhang, X., Du, M., Fang, H., Shi, M., Zhang, C., & Wang, F. (2021). Polymer-modified cement mortars: Their enhanced properties, applications, prospects, and challenges. *Construction and Building Materials*, 299, 124290.