

LIST OF FIGURES

Figure	Page
1 Illustration of Seebeck effect, adapted from Saini <i>et al.</i> , 2021	6
2 Illustration of Peltier effect, adapted from Saini <i>et al.</i> , 2021.....	7
3 Illustration to demonstrate Thomson effect (Morrison and Dejene, 2020).....	8
4 The thermogalvanomagnetic effects with different directions of involved para meters (Goldsmid, 2010).	19
5 Illustration of model a couple p-n pair refrigerator (Goldsmid, 2010).....	21
6 Illustration of model a couple p-n generator (Goldsmid, 2010)	23
7 Illumination of n-type and p-type of thermoelectric materials behaviour (Nabilasamiron, 2012).	24
8 Summary of ZT as a functional temperature of p-type and n-type of the rmo- electric materials, a) p-type thermoelectric materials and b) n-type thermoelectric materials (Rull-Bravo <i>et al.</i> , 2015).....	26
9 Schematic of sol-gel method step by step (Bokov <i>et al.</i> , 2021).	30
10 Schematic diagram illustrating the hot pressing technique (Moustafa et al., 2011).	31
11 DC magnetron sputtering and. Pulsed DC magnetron sputtering (Vaccoat, 2024).....	32
12 Illustration of Spark plasma sintering technique (Max Planck Institutes).	33
13 Illustration of quenching process after melting process.	34
14 Mechanical alloying with flat and crack bulk sample (Kumar <i>et al.</i> , 2022).	35
15 Schematic representation of solid-state reaction method (Sodhiya <i>et al.</i> , 2021).....	36
16 (a) Crystalline structure model of $Zn_{39}Sb_{30}$ and (b) Crystalline structure model of $Zn_{13}Sb_{10}$ (Zou <i>et al.</i> , 2015).	37
17 Crystalline structure model of Zn_6Sb_5 (Mayer <i>et al.</i> , 1978).	37
18 Calculated X-ray diffraction pattern yields of $Zn_{39}Sb_{30}$ model by using Boru's CIF- 7040405 (Borup <i>et al.</i> , 2016).	40
19 Calculated X-ray diffraction pattern yields of Zn_6Sb_5 model by using Jeffrey Snyder's CIF-cm0515505_si_001(Snyder <i>et al.</i> , 2004).	40
20 Calculated X-ray diffraction pattern yields of $Zn_{13}Sb_{10}$ model by using Yurij's CIF- 4001474 (Mozharivskyj <i>et al.</i> , 2006).	41

LIST OF FIGURES (Continued)

Figure	Page
21 XRD yields of ZnSd (top) and Zn ₄ Sb ₃ (bottom) were prepares by quenching method (Böttger <i>et al.</i> , 2011).	42
22 XRD pattern of β -Zn ₄ Sb ₃ with 0.6 at. % Zn rich via different sintered tempe ratures in vacuum (Lee and Lin, 2018).	43
23 XRD pattern of milled β -Zn ₄ Sb ₃ with different at. % Zn rich (Lee and Lin, 2018).	44
24 SEM images of β -Zn ₄ Sb ₃ powder; (a) Before mechanical alloying method and (b) After mechanical alloying method (Ur <i>et al.</i> , 2003).	44
25 SEM images of hot-pressed β -Zn ₄ Sb ₃ ceramic at temperatures of 373 K, 473 K, 573 K and 673 K with pressure 0.98 GPa (Lee and Lin, 2018).	45
26 SEM images of hot-pressed β -Zn ₄ Sb ₃ ceramic with pressing pressures of 100 MPa (a) and 200 MPa (b) at 673 K (Ahn <i>et al.</i> , 2011).	45
27 Seebeck coefficient, thermal conductivity and electrical conductivity of hot-pressed β -Zn ₄ Sb ₃ ceramic pellets via different temperatures and pressure (Ahn <i>et al.</i> , 2011).	46
28 Schematic of a dual leg TEG module and dual leg series TEG device with isotropic properties (Crawford, 2014).	47
29 Schematic of sing leg TEG module with isotropic properties (Crawford, 2014).	48
30 Schematic of serpentine and tilted-multilayer TTE module with anisotropic thermoelectric properties (Goldsmid, 2017).	48
31 (a) Photograph of misaligned make assembly equipment for sputtering Bi/Bi _{0.5} Sb _{1.5} Te ₃ TTE device, (b) Illustration of layer by layer stacking of Bi/Bi _{0.5} Sb _{1.5} Te ₃ (Mu <i>et al.</i> , 2019).	49
32 Tilted ceramic block TTE device prepared by La _{1.97} Sr _{0.03} CuO ₄ with silver paste connector (Dreßler <i>et al.</i> , 2015).	50
33 Schematic of dual leg, unileg and transverse series monolithic TEG device (Dreßler <i>et al.</i> , 2015).	51
34 Illustration of charge positions of all monolithic TEGs model.	51
35 Monolithic Ag ₂ S _{0.2} Se _{0.8} / Ag ₂ S /Bi _{0.5} Sb _{1.5} Te ₃ TEG modules.	52

LIST OF FIGURES (Continued)

Figure	Page
36 Process synthesis of β -Zn ₄ Sb ₃ powders: a) Premixed powders with zirconia balls were filled into a PP bottle, b) The filled PP bottle was rotated using roller milling machine, c) The mixture powders were calcined under Ar gas flowing, and d) Synthesized β -Zn ₄ Sb ₃ powders.....	54
37 The β -Zn ₄ Sb ₃ bulk pellets after were pressed at 500 and 700 MPa, respectively.....	56
38 The sintered β -Zn ₄ Sb ₃ pellets after were sintered at 500 °C, 550 °C, 575 °C and 600 °C for 6 hours.	57
39 The cyclical compression process for preparing β -Zn ₄ Sb ₃ /ZnO pellets.	59
40 The test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs versus weight size of β -Zn ₄ Sb ₃ pellets part.	59
41 Fabrication processes of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs: a) compressed multi-stacks β -Zn ₄ Sb ₃ /ZnO pellet, b) sintered multi-stacks β -Zn ₄ Sb ₃ /ZnO pellet, c) connected electrical wire with zigzags connection of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs, and d) monolithic β -Zn ₄ Sb ₃ TEGs was plastered with cement filler.	60
42 Shows x-ray incident and diffraction, according to Bragg's law (www.didaktik.physik.uni-muenchen.de/elektronenbahnen/en/index.php).....	62
43 Shows X-ray diffraction machine, D8-Bruker, SUT.....	62
44 Illustration of a x-ray absorption energies of K edge, L edges and M edges (Chem.libretexts, 2000).	63
45 Illustration of x-ray absorption transmission mode (Mit.edu, 2004).	64
46 Illustration of Seebeck coefficient and electrical resistivity (Linseis, 2024).	64
47 LINSEIS LSR-3 Seebeck type resistivity measurement system	65
48 The self-made heating/cooling system with IV measurement capabilities.	66
49 X-ray diffraction patterns of the synthesized β -Zn ₄ Sb ₃ powders under conditions of calcination temperature non-calcined, 300 °C, 400 °C and 500 °C without excess of Zn.....	68
50 The comparison XRD pattern of the synthesized β -Zn ₄ Sb ₃ powders under varying excessed Zn condition via calcination temperature 400 °C and held for 3 hours.....	69

LIST OF FIGURES (Continued)

Figure	Page
51 XRD pattern of varying holding time via excessing Zn of 10 at.% Zn and calcination temperature 400 °C.	70
52 The comparison XRD pattern of the synthesized β -Zn ₄ Sb ₃ powders under varying calcination temperature at 350 °C, 400 °C and 450 °C via adding 10 at.% Zn and calcination holding time for 3 hour.	71
53 Comparison XRD pattern of the synthesized β -Zn ₄ Sb ₃ powders under excessing Zn for 10, 11, 12, 13 and 14 at.% Zn and calcination at 450 °C for 3 hours.	72
54 Comparison XRD pattern of the synthesized β -Zn ₄ Sb ₃ powders under excessing Zn for 10, 11, 12, 13 and 14 at.% Zn and calcination at 400 °C for 3 hours.	73
55 Comparison XRD pattern of the synthesized β -Zn ₄ Sb ₃ powders under excessing Zn for 10, 11, 12, 13 and 14 at.% Zn and calcination at 425 °C for 3 hours.	74
56 Comparison of synthesis series of excessing Zn for 10, 11, 12, 13, 14 and 15 at.% Zn and calcination at 400 °C, 425 °C, 450 °C for 3 hours of.	75
57 Normalized XANES of Zn K-edge of the high pure synthesized β -Zn ₄ Sb ₃ powder.	76
58 Derivative normalized XANES of Zn K-edge of the high pure synthesized β -Zn ₄ Sb ₃ powder.	77
59 Normalized XANES of Sb L3, L2 and L1-edge of the high pure synthesized β -Zn ₄ Sb ₃ powder.	78
60 Derivative normalized XANES of Sb L3, L2 and L1-edge of the high pure synthesized β -Zn ₄ Sb ₃ powder.	79
61 Seebeck coefficient of the sintered β -Zn ₄ Sb ₃ pellets versus varying temperature.	81
62 Electrical resistivity of the sintered β -Zn ₄ Sb ₃ pellets versus varying temperature.	82
63 Electrical power factor of the sintered β -Zn ₄ Sb ₃ pellets versus varying temperature.	83
64 IV-curve of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs under condition of weight 1.0 g versus different operating Th and ΔT	83

LIST OF FIGURES (Continued)

Figure	Page
65 Electrical power output curves of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEG module under condition of weight 1.0 g versus different operating T_h and ΔT	87
66 IV characteristics of the monolithic multi-stack β -Zn ₄ Sb ₃ /ZnO TEGs versus varying operation hot side temperature and temperature gradients ΔT	89
67 Electrical power output curves of the monolithic multi-stack β -Zn ₄ Sb ₃ /ZnO TEGs versus varying operation hot side temperature and temperature gradients ΔT	91
68 IV-curve of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs under condition of weight 0.2 g versus different operating T_h and ΔT	107
69 IV-curve of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs under condition of weight 0.5 g versus different operating T_h and ΔT	108
70 IV-curve of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs under condition of weight 2.0 g versus different operating T_h and ΔT	109
71 IV-curve of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEGs under condition of weight 4.0 g versus different operating T_h and ΔT	110
72 Electrical power output curves of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEG module under condition of weight 0.2 g versus different operating T_h and ΔT	111
73 Electrical power output curves of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEG module under condition of weight 0.5 g versus different operating T_h and ΔT	112
74 Electrical power output curves of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEG module under condition of weight 2.0 g versus different operating T_h and ΔT	113
75 Electrical power output curves of the test cells of monolithic β -Zn ₄ Sb ₃ /ZnO TEG module under condition of weight 4.0 g versus different operating T_h and ΔT	114