

TABLE OF CONTENTS

	Page
ABSTRACT (THAI)	I
ABSTRACT (ENGLISH)	III
ACKNOWLEDGEMENTS	V
TABLE OF CONTENTS	VI
LIST OF TABLES	VIII
LIST OF FIGURES	IX
ABBREVIATIONS AND SYMBOLS	XIII
CHAPTER	
I INTRODUCTION.....	1
1.1 Statement of the problem	1
1.2 Objectives of the study	6
1.3 Organization of the dissertation.....	7
1.4 References.....	8
II LITERATURE REVIEW	13
2.1 Introduction	13
2.2 Ordinary Portland Cement.....	13
2.3 The Hydration Reaction	16
2.4 General features.....	21
2.5 Recycled Concrete Aggregate.....	24
2.6 Natural Rubber Latex (NRL) modified concrete	31
2.7 Fly Ash (FA) modified concrete.....	41
2.8 References.....	43
III ENHANCING THE FLEXURAL STRENGTH OF CONCRETE PAVEMENTS WITH RECYCLED AGGREGATE USING NATURAL RUBBER LATEX ADDITIVE.....	50

TABLE OF CONTENTS (Continued)

	Page
3.1 Introduction	50
3.2 Material and Methods	53
3.3 Results.....	60
3.4 Microstructural Analysis	68
3.5 Conclusion.....	72
3.6 References.....	73
IV FLY ASH AND NATURAL RUBBER LATEX MODIFIED RECYCLED AGGREGATE CONCRETE AS SUSTAINABLE RIGID PAVEMENT SURFACE.....	77
4.1 Introduction	77
4.2 Material and Methods.....	81
4.3 Results.....	87
4.4 Microstructural Analysis.....	102
4.5 Carbon emission and cost analyses.....	107
4.6 Conclusion.....	112
4.7 References.....	113
V CONCLUSIONS AND RECOMMENDATIONS.....	121
5.1 Summary and conclusions.....	121
5.2 Recommendations for future work.....	123
APPENDIX	
APPENDIX A. List of publications	125
BIOGRAPHY	157

LIST OF TABLES

Table	Page
2.1	the main composition of Portland cement..... 14
2.2	the physical and chemical properties of OPC 15
3.1	Chemical composition of ordinary Portland cement (OPC).....53
3.2	Chemical Analysis of Natural Rubber Latex55
3.3	Mixing Proportions of RCA-NRL Concrete (kg/m ³).....56
4.1	Chemical compositions of OPC and Fly Ash.....81
4.2	Chemical Analysis of Natural Rubber Latex82
4.3	The mix proportions of the FA-NRL-RCA concretes.....84
4.4	Emission factors (kg CO ₂ -e/kg) and Material Cost of concrete mix materials109

LIST OF FIGURES

Figure	Page
2.1 The SEM micrographs of OPC (Hongfang, 2015)	15
2.2 Contribution of Compressive strength of C_3S , C_2S , C_3A and C_4AF with time (Lerch, 2008)	18
2.3 The SEM images of C-S-H structure (Li, 2015)	19
2.4 The SEM images of CH structure (Wang, 2008; Frias, 2015)	20
2.5 The SEM images of (a) Ettringite (Frias, 2015) (b) Monosulfate (Choi, 2012)	21
2.6 Formation of the of hydration products and the creation of cement paste structure (Locher, 1974).....	21
2.7 Backscattered SEM image of a mature cement paste showing the main microstructural features	22
2.8 The ITZ between mortar and aggregate in concrete (Otsuki, 2003).....	22
2.9 Strength and porosity with different W/C ratios (Kim, 2014)	23
2.10 Chloride diffusion coefficient and porosity with different W/C ratios (Kim, 2014)	23
2.11 Chloride conductivity (Olorunsogo, 2002)	24
2.12 Pictorial representation of physical characteristics of recycled aggregate (Bahera, 2014)	25
2.13 Difference between matrixes of (a) natural aggregate concrete and (b) recycle aggregate concrete (Bahera, 2014).....	25
2.14 Micrograph of RAC structure (Thomas, 2013).....	26
2.15 Classification of aggregate, old mortar and new mortar by discoloration of phenolphthalein solution (Lee, 2013)	27
2.16 Variation in 28 days strength compressive strength w.r.t. RA replacement percentage by various researchers	27

LIST OF FIGURES (Continued)

Figure	Page
2.17	Mixing procedures of the (i) normal mixing approach and (ii) two-stage mixing approach (Tam, 2004)28
2.18	(a) Filled crack in RA using TSMA. (b) Unfilled crack in RA using NMA.....28
2.19	(a) New interfacial zone for TSMA. (b) Poorer new interfacial zone for NMA ..29
2.20	Compressive strength of concrete replacement by GFA and GBA30
2.21	Chloride penetration depth of concrete immersed in 3% sodium chloride solution at 6, 12, and 18 months30
2.22	RA structure after adopting (i) NMA, (ii) TSMA _s and (iii) TSMA _{sc}31
2.23	Compressive strength of NRL-concrete at (a) 7 days; (b) 14 days; (c) 28 days (Yaowarat et al., 2021)32
2.24	Flexural strength of NRL-concrete at (a) 7 days; (b) 14 days; (c) 28 days (Yaowarat et al., 2021)33
2.25	SEM images of NRL-concrete for w/c = 0.4 at (a) r/c = 0; (b) r/c = 1.16 (optimal); (c) r/c = 5.78. (Yaowarat et al., 2021)34
2.26	EDX results of NRL-concrete for w/c = 0.4 at (a) r/c = 0; (b) r/c = 1.16 (optimal); (c) r/c = 5.78.36
2.27	Flexural toughness of NRL concrete at different w/c and r/c ratios (Suddeepong et al., 2022)37
2.28	Comparison of total, elastic and plastic deformations behavior under repetitive flexural stress of NRL concrete for different r/c ratios at w/c ratio of (a) schematic plot; (b) 0.3%; (c) 0.4%; and (d) 0.5% (Suddeepong et al., 2022)38
2.29	(a) Influences of flexural strength on reduction in thickness of normal and NRL concretes; and (b) relationship between deformation and number of cycles at same stress ratio for different thickness and r/c ratios (Suddeepong et al., 2022)39

LIST OF FIGURES (Continued)

Figure	Page
2.30 Relationship between stress ratio and fatigue life of normal and NRL-concretes at different w/c and r/c ratios (Suddeepong et al., 2022)	39
2.31 Morphologies; (a) normal cement-sand matrix, (b) cement-sand with 10% latex, (c) cement-sand with 20% latex and (d) latex-film (Muhammad and Ismail, 2012).....	40
3.1 Particle size distributions of sand, Crushed Limestone, RCA and RCA + sand	54
3.2 (a) Specimen; (b) schematic of the dimensions for flexural test	59
3.3 Initial and final setting times of NRL- cement paste	60
3.4 Compressive strength of RCA-NRL concrete at (a) 7days; (b) 28 days	62
3.5 Flexural strength of RCA-NRL concrete at (a) 7days; (b) 28 days.....	64
3.6 Flexural strength and mid-span displacement of specimen cured at 28 days at w/c of (a) 0.3, (b) 0.4 and (c) 0.5	65
3.7 Flexural strength versus compressive strength at various r/c ratio at (a) 7 days; (b) 28 days.....	67
3.8 SEM images of NRL-RCA-concrete for w/c = 0.3 at (a) r/c = 0; (b) r/c = 1 (optimal); (c) r/c = 2	69
3.9 EDX results of NRL-concrete for w/c = 0.3 at (a) r/c = 0; (b) r/c = 1.0 (optimal); (c) r/c = 2.0	71
3.10 X-ray diffraction pattern of NRL-RCA-concrete at w/c =0.3 with r/c ratio of (a) 0%; (b) 1%; (c) 2% at 28 days	72
4.1 Particle size distributions of Sand, RCA, RCA+Sand and FA	82
4.2 Compressive strength of FA-RCA-NRL concrete at (a) 7 days; (b) 28 days; (c) 56 days	90
4.3 Flexural strength of FA-RCA-NRL concrete at (a) 7 days; (b) 28 days; (c) 56 days.	94

LIST OF FIGURES (Continued)

Figure	Page
4.4 Fatigue life of FA-RCA-NRL concrete at 28 days for FA replacement levels of (a) 15%, (b) 20%, and (c) 25%.....	95
4.5 Fatigue life of FA-RCA-NRL concrete at 56 days for FA replacement levels of (a) 15%, (b) 20%, and (c) 25%.....	96
4.6 Flexural fatigue response of FA-RCA-NRL concrete under a stress ratio of 60% after 56 days for FA replacement levels of (a) 15%, (b) 20%, and (c) 25%	100
4.7 Effect of r/b ratio on fatigue life versus SR_0 relationship of FA-RCA-NRL concrete at 56 days for varying fly ash replacement levels: (a) 15%, (b) 20%, and (c) 25%.	101
4.8 SEM images of FA-RCA-NRL concrete at 28 days with 25% fly ash replacement and r/b ratios of 0%, (b) 0.5% (optimal), and (c) 2%.....	104
4.9 SEM images of FA-RCA-NRL concrete at 56 days with 25% fly ash replacement and r/b ratios of 0%, (b) 0.5% (optimal), and (c) 2%.....	105
4.10 EDS images of FA-RCA-NRL concrete at 56 days with 25% fly ash replacement and r/b ratios of 0%, (b) 0.5% (optimal), and (c) 2%.....	106
4.11 FA-RCA-NRL concrete mixtures and corresponding 28-day compressive strength, flexural strength and fatigue life: (a) CO ₂ emissions and (b) material cost.....	110