

ACKNOWLEDGEMENT

First and foremost, I would like to express my heartfelt gratitude to my thesis advisor, Associate Professor Dr. Sarum Boonmee and my co-advisor, Professor Dr. Yasuhiro Matsubara, for their kind guidance, insightful feedback and for giving me the valuable opportunity to join the collaborative research program with the National Institute of Technology, Kurume College.

This research would not have been possible without the support and guidance of many individuals. I owe my deepest appreciation to Professor Dr. Yasuhiro Matsubara, whose mentorship shaped this work in countless ways. My sincere thanks also go to Associate Professor Dr. Sudsakorn Inthidech, for his continued guidance and support since I began my experiments at the Faculty of Engineering, Mahasarakham University. I am equally grateful to Professor Dr. Kaoru Yamamoto of the Department of Materials Science and Engineering, National Institute of Technology, Kurume College, for his valuable advice and for taking such good care of me during my stay there. I would also like to acknowledge Dr. Yuzo Yokomizo, Director of Kawara Steel Work Co., Ltd., for kindly providing the rubber wheel abrasive wear test.

I would also like to express my sincere gratitude to Suranaree University of Technology, for the scholarship and research funding that supported me throughout my doctoral studies, without which this research would not have been possible.

Finally, I wish to express my deepest gratitude to my family, especially my older sister, for her unwavering financial support and encouragement since I began my doctoral studies. This work would not have been possible without their constant support.

Krittapart Sriboonrueang